

- Input (1)**
 - Voltage (3)
 - RTD (3)
 - Resistance (3)
 - TC (3)
- Output (1)**
 - Current passive (3)
- Power supply options (1)**
 - Terminals (3)
- Supply voltage (1)**
 - Loop-powered (3)
- Mounting options (1)**
 - DIN rail (2)
 - Head-mounted (3)
- Approvals / conformity (1)**
 - CE (3)
 - ATEX (3)
 - IECEx (2)
 - EACEx (2)
 - cFM us (2)
 - INMETRO (2)
 - CSA (2)
 - NEPSI (2)
- Functional safety (1)**
 - SIL 2 Certified (3)
 - SIL 2 Certified / SIL 3 with redundant configuration (3)

Search result

[Clear all filters](#) Voltage Current passive Terminals Loop-powered Head-mounted ATEX SIL 2 Certified

3 product(s) found



2-wire HART 7 temperature transmitter 5437D

- RTD, TC, Ohm, and bipolar mV input
- Single or true dual inputs
- HART 7 and HART 5

[Add to quote list](#)
[View product](#)
[Add to comparison list](#)



2-wire HART 7 temperature transmitter 5437B

- RTD, TC, Ohm, and bipolar mV input
- Single or true dual inputs
- HART 7 and HART 5

[Add to quote list](#)
[View product](#)
[Add to comparison list](#)



2-wire HART 7 temperature transmitter 5437A

- RTD, TC, Ohm, and bipolar mV input
- Single or true dual inputs
- HART 7 and HART 5

[Add to quote list](#)
[View product](#)
[Add to comparison list](#)

VOORBEELD

[Klik Hier voor de Selector.](#)